

# OGM-A-25/40/50 铸铝椭圆齿轮流量计 Aluminum Oval Gear Meter



OGM25-A-1



OGM50-A-1



OGM25-DP-1



OGM25-EP-1

## ■ 概论

OGM-A-25/40/50铸铝椭圆齿轮流量计用来传输大黏度范围的液体，并具有很好的重处长性和使用寿命，可以广泛始于石油、化工、医药、交通、食品等工业及商业。


## Main Features

OGM-A-25/40/50 aluminum oval gear meter has the ability to handle a wide range of fluid viscosities with exceptional levels of repeatability and durability, applying in the petroleum, chemical, food industry, etc.

## ■ 优点

- 结构紧凑，维修容易
- 易读易操作的机械显示
- 水平或竖直灵活安装
- 压力损失小

## ■ 结构



## Advantage

- Compact size, easy maintenance
- Easy to read and operate mechanical display
- Horizontally and vertically flexibility of installation options
- Low pressure drop

## ■ 应用范围

用于石油、化工、医药、交通、食品等工业及商业

## Application

Widely used in industries of petroleum, chemical processing, medicine, transportation, food, etc.

### 包装数据 Package Data

型号 Model	OGM-A-25	OGM-A-40
净重 Net Weight	40×23×31cm	40×23×31cm
毛重 Gross Weight	8kg	10kg
包装尺寸 Dimension	9kg	11kg
包装 Package	4台/件纸箱4pcs/Carton	2台/件纸箱2pcs/Carton

### 技术参数 Technical Specification

型号 Model	OGM-A-25	OGM-A-40	OGM-A-50
公称直径 Size	1"	1.5"	2"
最小流量 Min.Flow Rate	20L/min	25L/min	30L/min
最大流量 Max.Flow Rate	200L/min	250L/min	300L/min
计量精度 Accuracy	±0.5%	±0.5%	±0.5%
重复度 Repeatability	≤0.03%	≤0.03%	≤0.03%
最大黏度 Max.Viscosity	1000CPS	1000CPS	1000CPS
最大工作压力 Max.Operating Pressure	3.4MPa	1.8MPa	1.8MPa